



LIGHT ELECTRONICS CO., LTD.




LT4540 is a dual-element Si photodiode which is moulded into a small plastic leadless optical package. Produced as one chip, the photodiodes offer a very good symmetry, low dark current and high sensitivity.

FEATURES

- · Low dark current
- · High sensitivity
- · Small surface mounting type

TYPICAL APPLICATIONS

- · Position sensors
- · Differential light measurement
- · Auto focus






KEY CHARACTERISTICS

Parameter	Value	Unit
Photodiode	(2)1.6× 1.0	mm
Peak wavelength	850	nm
Dark current@30 ,Vr=2V	1.0	nA

DIMENSIONS





Part No. LT4540 Pa

2 of 3



LIGHT ELECTRONICS CO., LTD.



Absolute Maximum Ratings (Ta=25)


Parameter	Symbol	Min.	Max.	Unit
Soldering temperature	T _{sol}		260	
Storage Temperature	T _{stg}	-30	90	
Operating Temperature	T _{opr}	-20	80	

Electro-Optical Characteristics (Ta=25)

Symbol	Parameter	Conditions	Min.	Тур.	Max.	Unit
A _{pd}	Active area	A1, A2 width height		1.60 1.00		mm
λ	Spectral response range		400		1100	nm
λ _{peak}	Peak sensitivity wavelength			850		nm
I _{sc}	Short circuit current	EV=1000 Lx *1		17		uA
Speak	Peak sensitivity			0.55		A/W
I _d	Dark current	C1,C2 Vr=10V			20	nA
C _j	Junction capacitance	C1,C2 Vr=10V		20		pF
θ	Half angle			65		deg.

^{*1.} Under tungsten lamp of color temp.=2856K

Spectral Sensitivity



 Part No.
 LT4540
 Page
 3 of 3